

26/01/21

HOLMES DTU**DETACHABLE TOWING UNIT**

The new Holmes D.T.U. (Detachable Towing Unit) offers proven design and technology from the oldest and most trusted name in the towing industry. The front legs allow the unit to be easily removed in a matter of minutes so your truck can be multi-functional for both towing or pulling trailers.

The D.T.U. is designed to secure to your truck using a front lock down bracket and your Fifth Wheel Plate. The power for the unit is provided by an optional wet line kit, with quick connect couplers, that is installed on your truck. Other popular options include a 20,000 lb. or 25,000 lb. planetary winch, tool boxes, and lanyard controls; all of which are available from your local Holmes distributor.



The D.T.U. has a retracted lift rating of 35,000 lbs. and a rating of 16,000 lbs. at its fully extended reach of 113". The unique design of the unit allows for reduced overhang behind the rear axle to provide better weight distribution and increased safe towing capacity.

DETACHABLE TOWING UNIT

SPECIFICATIONS

Lift Capacity	
Retracted	35,000 lbs.
Extended	16,000 lbs.
Reach Past Tailboard	
Fully Extended	113 inches
Fully Retracted	51 inches
Power Tilt Arc	20 degrees
Shipping Weight	
with out winch	4,550 lbs.
with 20,000 Winch	5,000 lbs.

STANDARD FEATURES & EQUIPMENT

- Power Elevation
- Power Extension
- Power Fold
- Power Tilt
- Front Stands
- Manual Controls
- 4 Sets of Frame Forks
- Fork Storage Holders
- Safety Chains
- Hook End Caps

OPTIONAL EQUIPMENT

- 20,000 lb Planetary Winch - w/ 150' x 9/16" IWRC Cable
- 25,000 lb Planetary Winch - w/ 200' x 5/8" IWRC Cable
(Winch Options Include: Air Tensioners, Air Free Spool, 360° Sheave Head, Air & Electrical Lines)
- Wet Line Kit - (PTO with pressure relief valve, pump, 15 Gallon Hydraulic Tank, Return Filter, Quick Disconnect, Fittings & Hoses)
- Hand Held Remote Control - 6 Function Controller with 25' Cord
- Emergency Lighting
- Work Area Lighting
- Remote Tailboard Control
- Switch Panel
- Tow Lights & Cord
- Tool Compartment
- Additional Lift Forks & Towing Attachments



Note: Some optional equipment may be shown. Other Holmes Towing & Recovery Equipment is Available from your local Holmes Distributor.

CHASSIS RECOMMENDATIONS

Minimum Wheelbase 250"

Minimum Clearance from front of D.T.U to Center of Trunnion . 84"

Note: Ratings are based on structural factors only - not chassis capacity. All chassis specifications are minimums, heavier specifications may be required depending on chassis and equipment weights. Holmes reserves the right, without notice and without obligation, to improve or modify products, which may change the specifications, models and feature availability.

